

# ATFX 375

SYNTHETIC ATF BOOSTER, ESTER BASED

## DESCRIPTION

ATFX 375 is a synthetic ATF fluid additive for Automatic and CVT transmissions. The synergy between unique synthetic ester complex fluid and high-tech performance additives, improve performance as well as thermal and oxidative stability of the hydraulic fluid.

## BASIC BENEFITS

- Improves shifting.
- Reduces wear.
- Seal protection.

## PROPERTIES

- Smoothens general operation and gear shifting.
- Significantly reduces friction and wear on all internal components.
- Protects under all conditions and extends the life of the transmission unit.
- Prevent leaks by maintaining optimum seal condition.
- Protects the oil from oxidation and maintains the transmission internally clean.
- Maintains hydrodynamic efficiency over a wide temperature range.
- Avoids overheating.

## APPLICATION

Compatible with all OEM recommended ATF fluids applied in automatic and CVT transmission systems. Suitable for cars, trucks, motorcycles and boats, as well as industrial engines.

### Recommendation:

For maximum effect and advisability first remove (before applying) the old ATF oil from the system and refill it with new Xenum ATF oil plus the ATFX 375 additive.

## DIRECTIONS OF USE

Add 1 can (375 ml) to the transmission system fluid. Dosage is sufficient for up to 10 liters of oil. Start the engine; shift the gears up and down. Check the transmission oil level.

## TYPICALS

Aggregation state	Liquid
Colour	Light brown
Pour point	-54 °C
Flash point	230 °C
Self ignition	Not selfigniting
Density	0.888 Kg/l
Viscosity at 40°C	53 mm <sup>2</sup> /s

## PACKAGING

375 ml can (12 x 375 ml/carton)

