

SEMIX 0w20

HYBRID SYNTHETIC MOTOR OIL

DESCRIPTION

Universal, fuel economy, specially composed hybrid synthetic motor oil recommended for use in petrol and diesel engines, with or without turbocharging, in passenger cars and delivery vans. Its exceptionally low viscosity allows it to be used the year round, also during very low temperatures in the wintertime.

PROPERTIES

- Very stable viscosity index.
- High resistance against shearing.
- Very safe cold start.
- Excellent fluidity at low temperature.
- Fuel economy and CO2 reduction.
- Strong resistance and protection against wear.
- Powerful detergency prevents deposits in the engine.
- Safe lubrication film.
- Very good detergency.

APPLICATION

This product has been specifically developed to meet the challenging requirements for hybrid cars, where fuel economy and CO2 reduction is important. It provides the performance needed for the most recent requirements for gasoline-fueled US and Asian (i.e. Honda, Toyota, Mitsubishi) passenger cars. Apply the correct amount of oil indicated in the operating instructions of the vehicle and engine manufacture.

TYPICALS

Density at 15 °C	0,846 kg/l
Viscosity -35 °C	5320 mPa.s
Viscosity 40 °C	46,70 mm ² /s
Viscosity 100 °C	8,54 mm ² /s
Viscosity index	162
Flash point COC	230 °C
Pour point	-48 °C
Total base number	9,7 mgKOH/g
Sulphated ash	1,22 %

SPECIFICATIONS

ACEA: A1/B1
API: SN/RC
ILSAC: GF-5
CHRYSLER: MS6395
FORD: M2C945-A/M2C946-A/M2C947-A

PACKAGING

1L can (12 x 1L box)
5L can (4 x 5L box)
20 L can
60 L drum
208 L drum

