

SEMIX 0w30

HYBRID SYNTHETIC MOTOR OIL

DESCRIPTION

Universal, fuel economy, specially composed hybrid synthetic motor oil recommended for use in petrol and diesel engines, with or without turbocharging, in passenger cars and delivery vans. Its exceptionally low viscosity allows it to be used the year round, also during very low temperatures in the wintertime.

PROPERTIES

- Very stable viscosity index.
- High resistance against shearing.
- Very safe cold start.
- Excellent fluidity at low temperature.
- Fuel economy and CO2 reduction.
- Strong resistance and protection against wear.
- Powerful detergency prevents deposits in the engine.
- Safe lubrication film.
- Very good detergency.

APPLICATION

This product is aimed and specially formulated for usage in diesel and gasoline engines of BMW group passenger vehicles. It can also be used in other OEM diesel and gasoline engines where there is a need for a 0W30 grade low SAPS oil.

TYPICALS

Density at 15 °C	0,854 kg/l
Viscosity -35 °C	5930 mPa.s
Viscosity 40 °C	51,50 mm ² /s
Viscosity 100 °C	11,00 mm ² /s
Viscosity index	182
Flash point COC	230 °C
Pour point	-45 °C
Total base number	10,5 mgKOH/g
Sulphated ash	1,33 %

SPECIFICATIONS

ACEA: A3/B4
API: SN/CF
MB 229.3/226.5
VW 502.00/505.00
BMW Longlife-01
Renault RN0700

PACKAGING

1L can (12 x 1L box)
5L can (4 x 5L box)
20 L can
60 L drum
208 L drum

