

# SEMIX 5w20

HYBRID SYNTHETIC MOTOR OIL

## DESCRIPTION

Universal, fuel economy, specially composed hybrid synthetic motor oil recommended for use in petrol and diesel engines, with or without turbocharging, in passenger cars and delivery vans.

## PROPERTIES

- High and stable viscosity index.
- High resistance against shearing.
- Very fast and safe cold start.
- Excellent fluidity at low temperature.
- Fuel economy and CO2 reduction.
- Strong resistance and protection against wear.
- Powerful detergency prevents deposits in the engine.
- Safe lubrication film.
- Very strong resistance against oxidation.

## APPLICATION

A fuel economy, special composed synthetic motor oil recommended for use in petrol engines of passenger cars, which prescribe an oil with the specification GM dexos1™ Gen 2.

## TYPICALS

Density at 15 °C	0,852 kg/l
Viscosity -30 °C	3940 mPa.s
Viscosity 40 °C	48,00 mm <sup>2</sup> /s
Viscosity 100 °C	8,80 mm <sup>2</sup> /s
Viscosity index	166
Flash point COC	226 °C
Pour point	-33 °C
Total base number	8,5 mgKOH/g
Sulphated ash	0,89 %

## SPECIFICATIONS

API SN, API SN Plus  
API SN Plus Resource Conserving  
ILSAC GF-5  
GM dexos1 (TM) Gen 2  
Chrysler MS 6395

## PACKAGING

1L can (12 x 1L box)  
5L can (4 x 5L box)  
20 L can  
60 L drum  
208 L drum

