

## PRO 0w40

HIGH PERFORMANCE FULL SYNTHETIC ENGINE OIL

### DESCRIPTION

Synthetic high performance engine oil produced with special selected base oils with a high viscosity index and a well balanced choice of advanced additives. Provides optimum protection and extended engine life and reliability. Combines exceptional anti-wear performance and outstanding high temperature protection with excellent cold start characteristics.

### PROPERTIES

- Fuel economy and CO2 reduction.
- High and very stable viscosity index.
- Very fast cold start.
- Safe lubrication film at extreme temperatures.
- Flexible and extended oil drain intervals.
- High protection against wear.

### APPLICATION

All 4-stroke gasoline engines, four-valve, turbocharged, and 4-stroke diesel engines with or without turbo. This oil is not suitable for diesel particulate filters.

### TYPICALS

Density at 15 °C	0,846 kg/l
Viscosity -35 °C	6000 mPa.s
Viscosity 40 °C	83,70 mm <sup>2</sup> /s
Viscosity 100 °C	14,00 mm <sup>2</sup> /s
Viscosity index	173
Flash point COC	232 °C
Pour point	-46 °C
Total base number	10,5 mgKOH/g
Sulphated ash	1,33 %

### SPECIFICATIONS

ACEA A3/B4  
API SN  
BMW LONGLIFE-01  
MB 229.5  
VW 502.00, 505.00  
Porsche A40  
Renault RN 0700, RN 0710

### PACKAGING

1L can (12 x 1L box)  
5L can (4 x 5L box)  
20 L can  
60 L drum  
208 L drum

