

PRO-C4 5w30

HIGH PERFORMANCE FULL SYNTHETIC ENGINE OIL

DESCRIPTION

Synthetic high performance engine oil produced with special selected base oils with a high viscosity index and a well balanced choice of advanced additives. Provides optimum protection and extended engine life and reliability. Combines exceptional anti-wear performance and outstanding high temperature protection with excellent cold start characteristics. This motor oil also contributes to the extension of the lifetime of particle filters.

PROPERTIES

- Fuel economy.
- Very stable viscosity index.
- Superior resistance against shearing.
- Fast cold start.
- Safe lubrication film at extreme temperatures.
- Flexible and extended oil drain intervals.
- High protection against wear.
- Low SAPS / DPF- compatible.

APPLICATION

A fuel economy, specially composed synthetic motor oil, recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. Due to its special composition this product can be applied in vehicles for which the Renault specification RN0720 is asked and are equipped with modern three way catalysts and diesel particle filters. Due to its low SAPS content this motor oil contributes to the extension of the lifetime of particle filters for diesel engines.

TYPICALS

Density at 15 °C	0,851 kg/l
Viscosity -30 °C	6320 mPa.s
Viscosity 40 °C	69,10 mm ² /s
Viscosity 100 °C	11,70 mm ² /s
Viscosity index	165
Flash point COC	222 °C
Pour point	-45 °C
Total base number	7,2 mgKOH/g
Sulphated ash	0,5 %

SPECIFICATIONS

ACEA C3/C4
MB 226.51 / 229.51
FIAT 9.55535-S4
Renault Rn 0720

PACKAGING

1L can (12 x 1L box)
5L can (4 x 5L box)
20 L can
60 L drum
208 L drum

