

X-TRAN 75W90

SYNTHETIC BASED MULTI GRADE TRANSMISSION OIL

DESCRIPTION

Supreme performance, synthetic based multi-purpose, SAE 75W-90 automotive gear lubricant designed to meet the highest level performance requirements of modern passenger vehicles in all types of operating conditions. Compared to conventional hypoid gear lubricants, X-TRAN 75w90 performs exceptionally over a wide range of temperatures. It also can be used in extended service and for aiding in fuel economy performance.

PROPERTIES

- Exceptional thermal stability and resistance to high temperature oxidation.
- Maintains film strength for reliable lubrication.
- Exceptional shear stability.
- Excellent rust, staining and corrosion protection of copper and its alloys.
- Outstanding protection against low speed/high torque wear and against high speed scoring.
- Enhanced frictional properties.
- Reduced wear & longer component life.

APPLICATION

For manual gearboxes, power steering units, torque converters and other hydraulic equipment. Apply the correct amount of oil indicated in the service instructions of the manufacture. Wrong amount of oil can cause damage to the transmission.

TYPICALS

Density at 15 °C, kg/l	0,879
Viscosity 40 °C, mm ² /s	83,00
Viscosity 100 °C, mm ² /s	14,80
Viscosity index	188
Flash point COC, °C	180
Pour point, °C	-45

SPECIFICATIONS

API GL-4/5
MIL-L-2105
Meets the requirements of
VW 501.50

PACKAGING

1L can (12 x 1L box)
60 L drum
208 L drum

