

AIRCO FIX

SEALING ADDITIVE TO REPAIR MICROLEAKS IN A/C SYSTEMS.

DESCRIPTION

The leak stop is a special sealing additive formulated for repair micro leaks in AC/R systems. This product allows easy and fast actions. The concentrated airco fix with UV fluorescent substance (8 ml) is ideal for one treatment.

PROPERTIES

- Ease of use.
- Fast and effective repair.
- It does not damage the various components and materials of the system.
- Perfectly compatible and miscible with the used refrigerant in the system.
- Not flammable.

APPLICATION

PREVENTIVE VERIFICATION TEST

1. Create A/C system vacuum for 5 minutes.
2. By vacuumeter, check the reaching of at least "-1 bar" value and that the value is maintained for at least 4 minutes (required condition). If it is not possible to maintain this value, the loss is too great to be repaired.

INSTRUCTION OF USE

1. Turn on the air conditioner.
2. Connect the adapter to the syringe and press the pistone to completely exit the air contained inside.
3. Connect the syringe to the low pression side.
4. Press the piston and inject until the complete evacuation of the liquid, then disconnect.
5. Leave the A/C systems work for at least 15/20 minutes, allowing the Airco Fix to enter in the system and act.

PACKAGING

Box containing a syringe (8ml)

Box containing a syringe (8ml) and adaptor for R1234YF systems

Box containing a syringe (8ml) and adaptor for R134a systems

Bag with 6 syringes (8ml) and 2 adaptors (1x R134a and 1x R1234YF)

