

ATFX 200

SYNTHETIC ATF BOOSTER, ESTER BASED

DESCRIPTION

ATFX 200 is a synthetic ATF fluid additive for Automatic and CVT transmissions. The synergy between unique synthetic ester complex fluid and high-tech performance additives, improve performance as well as thermal and oxidative stability of the hydraulic fluid.

BASIC BENEFITS

- Improves shifting.
- Reduces wear.
- Seal protection.

PROPERTIES

- Smoothens general operation and gear shifting.
- Significantly reduces friction and wear on all internal components.
- Protects under all conditions and extends the life of the transmission unit.
- Prevent leaks by maintaining optimum seal condition.
- Protects the oil from oxidation and maintains the transmission internally clean.
- Maintains hydrodynamic efficiency over a wide temperature range.
- Avoids overheating.

APPLICATION

Compatible with all OEM recommended ATF fluids applied in automatic and CVT transmission systems. Suitable for cars, trucks, motorcycles and boats, as well as industrial engines.

Recommendation:

For maximum effect and advisability first remove (before applying) the old ATF oil from the system and refill it with new ATF oil plus the ATFX 200 additive.

DIRECTIONS FOR USE

Add 1 tube (200 ml) to the transmission system fluid. Dosage is sufficient for up to 5 liters of oil. Start the engine; shift the gears up and down. Check the transmission oil level.

TYPICALS

Form:	Liquid
Colour:	Light brown
Boiling point/Boiling range:	Undetermined.
Pour point:	-54 °C
Flash point:	230 °C
Flammability (solid, gaseous):	Not applicable.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Density at 20 °C:	0.888 g/cm ³
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water):	Not determined.
Viscosity at 40 °C:	53 mm ² /s

PACKAGING

200 ml tube (12 x 200 ml carton)

