

BELT CONDITIONER

BELT SPRAY

DESCRIPTION

Specially designed for efficient treatment of variety of belts of engines and transmissions in different kind of machines, to avoid slipping and squeaking due to heat, cold, dust, humidity and aging.

BASIC BENEFITS

- Stops & prevents slipping and squeaking.
- Improves reliability of belts and driving wheels.
- Assures proper gear ratio and functioning.

PROPERTIES

- Penetrates into the cord fibres and provides long term effect.
- Increases grip.
- Increases belt flexibility and pliability.
- Extends belt life.

APPLICATION

For all V-, round, flat, V-ribbed and ribbed power belts.
Shake well before use. Hold spray can approximately 5 - 10 cm from the surface to be applied.
Recommended to use at each engine service to increase belt reliability.



TYPICALS

Form:	Aerosol
pH-value:	Not determined.
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	-44°C
Flash point:	-97°C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	200°C
Decomposition temperature:	Not determined.
Vapour pressure at 20°C:	4 Bar
Density at 20°C:	0.621 g/cm ³
Solubility in / Miscibility with water:	Not miscible or difficult to mix.

PACKAGING

500 ml aerosol (12 x 500 ml carton)