

C1200 +

ADVANCED CERAMIC COMPOUND SPRAY

DESCRIPTION

Professional ceramic lubricant aerosol. Provides reliable lubrication and protection of parts exposed to high temperatures.

BASIC BENEFITS

- Provides high temperatures resistant protection and lubrication of parts.
- Provides reliable protection against corrosion and wear.
- Easy to use.

PROPERTIES

- Free of aluminium, lead, copper, MoS₂, and sulphur.
- Resists chemical reactions of the thread compound with thread materials.
- Service temperature: -40°C to 1200°C.

APPLICATION

- Brakes, exhaust and turbo systems, turbine bolts.
- Lubrication of lambda sensor threads.
- High temperature threads in the chemical industry, refineries, and power plants.
- Assembly paste for bolts and sliding rails at high temperatures.

Shake well before use. Spray onto surface or parts. Clean parts and surface before applying the ceramic compound. Do not apply where grease is required.



TYPICALS

Form:	Aerosol
pH-value:	Not determined.
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	-44°C
Flash point:	-97 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	> 200 °C
Decomposition temperature:	Not determined.
Vapour pressure at 20°C:	8300 hPa
Density at 20°C:	0.658 g/cm ³
Solubility in / Miscibility with water:	Not miscible or difficult to mix.

PACKAGING

500 ml aerosol (12 x 500 ml carton)