

# CHAIN PRO

## HIGH PERFORMANCE SYNTHETIC CHAIN LUBRICANT + CERFLON®

### DESCRIPTION

Chain Pro has an ultra penetrative, anti-corrosive synthetic formulation reinforced with Cerflon®. Ensures complete chain protection in all conditions.

### BASIC BENEFITS

- Reduces power loss and wear throughout the drive system by providing unequalled lubrication to all moving parts.
- Adheres to the chain even at extreme speeds.
- Waterproofs and displaces moisture.
- Extends chain and sprocket life.

### PROPERTIES

- Reliable protection against rust and corrosion.
- Outstanding penetration properties.
- Temperature range: -40°C to +250°C.
- Behaves neutral against non-metallic materials such as varnish, plastic, rubber.

### APPLICATION

For all standard and with O-RING, X-RING and Z-RING chains from motorcycles, go-karts and industrial power drives. Shake well before use. Apply to the whole length of the inner chain. Adheres completely after a few minutes. Do not spray empty the valve. In general, CHAIN PRO does not need to be removed for further treatment (except painting). CHAIN-PRO can be removed without difficulty with cleaning materials.



### TYPICALS

Form:	Aerosol
pH-value:	Not determined.
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	-44°C
Flash point:	-97 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	200 °C
Decomposition temperature:	Not determined.
Vapour pressure at 20°C:	4 Bar
Density at 20°C:	0.725 g/cm <sup>3</sup>
Solubility in / Miscibility with water:	Not miscible or difficult to mix.

### PACKAGING

500 ml aerosol (12 x 500 ml carton)