

DRY GLISS

PTFE DRY LUBRICANT

DESCRIPTION

Dry Gliss is a high quality special lubricative product based on PTFE and solvents.

BASIC BENEFITS

- Weather Resistant, for outside and inside use.
- Performs non-greasy and non-oily lubrication.
- Protects against wear.
- Protects surfaces from corrosion.

PROPERTIES

- Excellent adhesion, high lubricity and extreme pressure properties.
- Provides reliable protective microfilm on surfaces.
- Represses rust.
- Acts as a water-repellent.
- Silicone free product.

APPLICATION

Dry Gliss Lubricant can be used for: lubrication in metalworking operations.

Lubrication of plastics and elastomers in drive belts, gaskets, gears, bearings and sleeves, and chain drives.

Can also be used as release agent in processes involving the moulding of rubber and plastic parts.

Shake well before use. Substrates should be clean and dry. Spraying distance approximately 20 cm.



TYPICALS

Form:	Aerosol
pH-value:	Not determined.
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	-44 °C
Flash point:	-97 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	200 °C
Decomposition temperature:	Not determined.
Vapour pressure at 20°C:	4 Bar
Density at 20°C:	0.65 g/cm ³
Solubility in / Miscibility with water:	Not miscible or difficult to mix.

PACKAGING

500 ml aerosol (12 x 500 ml carton)