

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Xenum Valvex

Print date: 07.08.2015

Page 1 of 8

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Xenum Valvex, REF 3260250

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Solvent mixture

#### 1.3. Details of the supplier of the safety data sheet

Company name:	XENUM N.V.	
Street:	Steenkaaistraat 17	
Place:	B-9200 Dendermonde	
Telephone:	+32 52 223808	Telefax: +32 52 22 51 60
e-mail:	info@xenum.eu	
Contact person:	Peter Tossyn	

#### 1.4. Emergency telephone number:

+32 479 82 08 08

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Directive 67/548/EEC or 1999/45/EC

Indications of danger: Xn - Harmful  
 R phrases:  
 Harmful: may cause lung damage if swallowed.  
 Repeated exposure may cause skin dryness or cracking.

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazard categories:  
 Skin corrosion/irritation: Skin Irrit. 2  
 Serious eye damage/eye irritation: Eye Dam. 1  
 Aspiration hazard: Asp. Tox. 1  
 Hazard Statements:  
 May be fatal if swallowed and enters airways.  
 Causes skin irritation.  
 Causes serious eye damage.

#### 2.2. Label elements

##### Hazardous components which must be listed on the label

Low boiling point hydrogen treated naphtha, Naphtha (petroleum), hydrotreated heavy potassium 1,2-bis(2-ethylhexyloxycarbonyl)ethanesulphonate  
 Distillates (petroleum), hydrotreated light, Kerosine - unspecified

Signal word: Danger

Pictograms: GHS05-GHS08



##### Hazard statements

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Xenum Valvex

Print date: 07.08.2015

Page 2 of 8

### Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P302+P352	IF ON SKIN: Wash with plenty of water.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

### Special labelling of certain mixtures

Operate if possible out of doors or in a well-ventilated place.

### Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

### 2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Preparation on the basis of hydrocarbons

#### Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
REACH No		
265-150-3	Low boiling point hydrogen treated naphtha, Naphtha (petroleum), hydrotreated heavy	80 - < 85 %
64742-48-9	Xn - Harmful R65-66	
	Asp. Tox. 1; H304 EUH066	
01-2119457273-39		
231-308-5	potassium 1,2-bis(2-ethylhexyloxycarbonyl)ethanesulphonate	10 - < 15 %
7491-09-0		
	Skin Irrit. 2, Eye Dam. 1; H315 H318	
265-149-8	Distillates (petroleum), hydrotreated light, Kerosine - unspecified	5 - < 10 %
64742-47-8	Xn - Harmful R65	
649-422-00-2	Asp. Tox. 1; H304	
01-2119484819-18		

Full text of R-, H- and EUH-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

If victim is at risk of losing consciousness, position and transport on their side. Provide fresh air.

#### After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Xenum Valvex

Print date: 07.08.2015

Page 3 of 8

### After contact with skin

After contact with skin, wash immediately with: Water and soap.

### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

### After ingestion

Give nothing to eat or drink. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur: Allergic reactions.

### 4.3. Indication of any immediate medical attention and special treatment needed

Hazards identification: Lung irritation.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Sand.

#### Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

In case of fire and/or explosion do not breathe fumes. In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide.

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

### Additional information

Co-ordinate fire-fighting measures to the fire surroundings.

Fire class B: Burning liquid or melting substances.

Move undamaged containers from immediate hazard area if it can be done safely.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Keep away from unprotected people. Keep upwind. Wear personal protection equipment. (refer to chapter 8) Eliminate all ignition sources if safe to do so.

### 6.2. Environmental precautions

Spilled product must not leak into the ground. Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### 6.3. Methods and material for containment and cleaning up

Suitable material for taking up: diatomaceous earth. Do not rinse down with water.

### 6.4. Reference to other sections

See protective measures under point 7 and 8.

Treat the recovered material as prescribed in the section on waste disposal.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Provide adequate ventilation as well as local exhaust at critical locations.

#### Advice on protection against fire and explosion

If handled uncovered, arrangements with local exhaust ventilation should be used if possible. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Vapours of flammable solvents can accumulate in the gas phase of closed container, especially during heat treatment. Therefore keep away from fire and sources of ignition.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Xenum Valvex

Print date: 07.08.2015

Page 4 of 8

#### Further information on handling

Avoid contact with skin and eyes.  
Take precautionary measures against static discharges.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Store only in original container.

##### Advice on storage compatibility

Keep away from food, drink and animal feedingstuffs. Keep away from sources of ignition. - No smoking.

##### Further information on storage conditions

Suitable floor material: Solvent-proof.

#### 7.3. Specific end use(s)

Observe technical data sheet.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### 8.2. Exposure controls



##### Appropriate engineering controls

Refer to chapter 7. No further action is necessary.

##### Protective and hygiene measures

Do not eat, drink, smoke or sneeze at the workplace.  
Street clothing should be stored separately from work clothing.

##### Eye/face protection

Suitable eye protection: Tightly sealed safety glasses. gemäß DIN EN 166

##### Hand protection

Tested protective gloves are to be worn: nach DIN EN 374  
Suitable material:  
NBR (Nitrile rubber).  
Thickness of glove material:: 0,45 mm; penetration time (maximum wearing period): 480 min  
NR (Natural rubber (Caoutchouc), Natural latex).  
Thickness of glove material:: 0,45 mm; penetration time (maximum wearing period): 10 min  
CR (polychloroprenes, Chloroprene rubber).  
Thickness of glove material:: 0,75 mm; penetration time (maximum wearing period): 60 min

Additional protection measures for the hands: Before using check leak tightness / impermeability.

##### Skin protection

Wear suitable protective clothing.

##### Respiratory protection

Respiratory protection necessary at: insufficient absorption. und prolonged action.  
gas filtering equipment (EN 141). A2 (brown)  
Use only respiratory protection equipment with CE-symbol including four digit test number.  
Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Xenum Valvex

Print date: 07.08.2015

Page 5 of 8

#### SECTION 9: Physical and chemical properties

##### 9.1. Information on basic physical and chemical properties

Physical state: liquid  
 Colour: colourless  
 Odour: characteristic

##### Test method

pH-Value: Not applicable.

##### Changes in the physical state

Melting point: - 20 °C  
 Initial boiling point and boiling range: 200 °C DIN 53171  
 Flash point: 65 °C DIN 51755

##### Flammability

Solid: Undetermined.  
 Gas: Undetermined.

##### Explosive properties

not Explosive.

Lower explosion limits: 0,6 vol. %  
 Upper explosion limits: 7 vol. %  
 Ignition temperature: >200 °C DIN 51794

##### Auto-ignition temperature

Solid: Undetermined.  
 Gas: Undetermined.

Decomposition temperature: Undetermined.

##### Oxidizing properties

not oxidizing.

Vapour pressure: 0,95 hPa DIN 51754  
 (at 20 °C)

Density (at 20 °C): 0,8 g/cm<sup>3</sup> DIN 51757

Water solubility: not miscible  
 (at 20 °C)

##### Solubility in other solvents

aliphatic hydrocarbons

Partition coefficient: Undetermined.

Viscosity / kinematic: 1,45 mm<sup>2</sup>/s  
 (at 40 °C)

Flow time: 3 DIN EN ISO 2431

Vapour density: Undetermined.

Evaporation rate: Undetermined.  
 (at 20 °C)

Solvent content: 80,00 %

##### 9.2. Other information

Solid content: 14,00 %

#### SECTION 10: Stability and reactivity

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Xenum Valvex

Print date: 07.08.2015

Page 6 of 8

#### 10.1. Reactivity

In case of warming: Explosion hazard.

#### 10.2. Chemical stability

The product is stable.

#### 10.3. Possibility of hazardous reactions

In case of warming: Explosion hazard.

#### 10.4. Conditions to avoid

heat.

In case of warming: Risk of selfignition.

#### 10.5. Incompatible materials

Oxidizing agents.

#### 10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
64742-48-9	Low boiling point hydrogen treated naphtha, Naphtha (petroleum), hydrotreated heavy				
	oral	LD50	5000 mg/kg	Rat	
	dermal	LD50	> 5000 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50	4951 mg/l	Rat	

##### Irritation and corrosivity

After skin contact: In case of skin irritation, seek medical treatment.

May cause respiratory irritation.

Practical experience.

##### Sensitising effects

May cause sensitisation by skin contact.

##### Severe effects after repeated or prolonged exposure

Has de-greasing effect on the skin. Frequently or prolonged contact with skin may cause dermal irritation.

##### Specific effects in experiment on an animal

No information available.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Acute fish toxicity LC50: 100-1000 g/m<sup>3</sup> (96 h) *Oncorhynchus mykiss*

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Xenum Valvex

Print date: 07.08.2015

Page 7 of 8

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h]   [d]	Species	Source
64742-48-9	Low boiling point hydrogen treated naphtha, Naphtha (petroleum), hydrotreated heavy					
	Acute fish toxicity	LC50	> 1000 mg/l	96 h	Oncorhynchus mykiss	
	Acute algae toxicity	ErC50	> 1000 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50	> 1000 mg/l	48 h	Daphnia magna	
64742-47-8	Distillates (petroleum), hydrotreated light, Kerosine - unspecified					
	Acute fish toxicity	LC50	> 100 mg/l	96 h		

#### 12.2. Persistence and degradability

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64742-48-9	Low boiling point hydrogen treated naphtha, Naphtha (petroleum), hydrotreated heavy			
	OECD 301F	80%	28	

#### 12.3. Bioaccumulative potential

No indication of bio-accumulation potential.

#### 12.4. Mobility in soil

No information available.

#### 12.5. Results of PBT and vPvB assessment

No information available.

#### 12.6. Other adverse effects

AOX: The product contains no organically bound Halogen.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### **Advice on disposal**

Carry out a burning of hazardous waste according to official regulations.

##### **Waste disposal number of waste from residues/unused products**

140603 WASTE ORGANIC SOLVENTS, REFRIGERANTS AND PROPELLANTS (except 07 and 08); waste organic solvents, refrigerants and foam/aerosol propellants; other solvents and solvent mixtures  
Classified as hazardous waste.

### SECTION 14: Transport information

#### Land transport (ADR/RID)

##### **Other applicable information (land transport)**

No dangerous good in sense of these transport regulations.

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### **EU regulatory information**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Xenum Valvex**

Print date: 07.08.2015

Page 8 of 8

2010/75/EU (VOC): 80 % (640 g/l)

**Additional information**

Sources of the most important data: 2001/118/EG, 1999/45/EG, 91/155/EWG, 67/548/EWG, (EG) 1907/2006, (EG) 1272/2008, GefStoffV, WRMG, WHG, TRG 300, TRGS 200, TRGS 220, ADR 2013, IMDG-Code

**National regulatory information**

Employment restrictions: Observe employment restrictions for young people. Observe employment restrictions for child bearing mothers and nursing.

Water contaminating class (D): 2 - water contaminating

**15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 1,2,9,14,15.

**Relevant R-phrases (Number and full text)**

- 65 Harmful: may cause lung damage if swallowed.  
66 Repeated exposure may cause skin dryness or cracking.

**Relevant H- and EUH-phrases (Number and full text)**

- H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
EUH066 Repeated exposure may cause skin dryness or cracking.

**Further Information**

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*