

# X-BRAKE DOT 4

## SUPER SYNTHETIC BRAKE FLUID

### DESCRIPTION

X-Brake DOT 4 is a premium quality, thin-bodied synthetic brake fluid. Especially developed for the new generation of cars with electronic safety systems such as ABS, ASR, ESP, EBD, BAS and all their variants. X-Brake DOT 4 offers a substantially higher safety margin than when ordinary DOT 4 brake fluids are used.

### BASIC BENEFITS

- Reliable operational safety in severe driving conditions.
- Fast response time, even at extremely low temperatures.
- Good resistance against ageing.

### PROPERTIES

- High wet boiling point.
- Very good compatibility with seals and gaskets.
- Minimal corrosion tendency.
- Very low viscosity, even under very low temperature.

### APPLICATION

For use in automotive disc, drum and anti-skid brake systems and clutch systems. Applicable in modern as well as older model automotive and commercial vehicles requiring DOT 3 or DOT 4 level of performance.

Suitable for cars with electronic safety systems such as ABS, ASR, ESP, EBD, BAS and all their variants. X-Brake DOT 4 can be mixed with other DOT 4 brake fluids without any difficulty.

### DIRECTIONS FOR USE

- Use only in its concentrated form out of a previously unopened or well sealed container.
- Always seal the container immediately after use as the fluid absorbs moisture from the atmosphere quite rapidly, this will reduce service life significantly.
- Never reuse drained brake fluid.
- Brake fluid can affect the vehicle paintwork, so remove spills immediately without rubbing.
- Brake fluid should be drained from the vehicle every two years or 40,000 Km (24,000 Miles) and refilled.
- Check Owners Operators Manual for details.

### TYPICALS

Density at 15 °C, kg/l	1,030
Viscosity -40 °C, mm <sup>2</sup> /s	1200
Viscosity 100 °C, mm <sup>2</sup> /s	2,30
Boiling Point (reflux) , °C	263
Wet Boiling Point, °C	168
pH - 50% in ethanol solution	8,0

### SPECIFICATIONS

SAE J 1703
FMVSS 116 DOT 4
ISO 4925



### PACKAGING

500 ml can (12 x 500ml carton)