

XC-LUBE

HIGH PERFORMANCE PENETRATING OIL + CERFLON®

DESCRIPTION

High-tech multi-purpose product containing the advanced Cerflon® reinforced lubricant. Obtains exceptional lubricative and protective properties even in severe applications. The combination of specific base oils, high performance additives and Cerflon® provides exceptional lubricating and protective properties due to its significant adhesion capacity (non visco-elastic).

BASIC BENEFITS

- Lubricates and reduces friction and wear in moving parts
- Eliminates squeaks
- Waterproofs and displaces moisture
- Universal applications



PROPERTIES

- Provides outstanding and long-term protection against oxidation and corrosion
- Excellent penetration
- Withstands high pressures
- Resists to cold, hot and salt water.

APPLICATION

All-purpose lubrication and long term protection of parts such as: chains, wire ropes, slides, conveyors, bearings, machinery, open gears, linkages, pulleys etc...

For industry, workshop, farming, marine, motorcycles, bicycles, and more.

Shake well before use. Do not spray empty the valve. Spray onto surface or parts and leave to penetrate.

If necessary, XC-LUBE can be removed without difficulty with cleaning materials.

In general, XC-LUBE does not need to be removed for further treatment (except painting).

TYPICALS

Form:	Aerosol
Boiling point/Boiling range:	- 44°C
Flash point:	- 97°C
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Vapour pressure at 20°C:	8300 hPa
Density at 20°C:	0.75700 g/cm ³
Solubility in / Miscibility with water:	Not miscible or difficult to mix.

PACKAGING

500 ml aerosol (12 x 500 ml carton)