

ZINC COAT +

GALVANISING COMPOUND – ZINC (ZN) SPRAY

DESCRIPTION

Zinc spray is a professional product, providing long term stable protection from corrosion on ferrous metals. The high content of zinc in this spray assures excellent cathodic protection.

BASIC BENEFITS

- Easy to use.
- Fast drying.
- Universal application.

PROPERTIES

- Forms reliable protective coating.
- High temperature resistance (up to 500°C).
- Content more than 90% Zinc (Zn).

APPLICATION

Can be used as a primer prior to painting.
It dries to the touch in 15 min. completely dry and paintable in 12 – 24 hours.
Especially suitable for protecting welds on galvanised parts.

Shake well before use (2-3 min). Spray heavily onto the items to be cleaned. Hold spray can approximately 20-30 cm from the surface. Use on a clean and corrosion free surface.
When finished, turn the aerosol and spray to have a clean nozzle.



TYPICALS

Form:	Aerosol
pH-value:	Not determined.
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	-44°C
Flash point:	-97 °C
Self-igniting:	Product is not selfigniting.
Ignition temperature:	450 °C
Vapour pressure at 20°C:	8300 hPa
Density at 20°C:	1.28 g/cm ³
Solubility in / Miscibility with water:	Not miscible or difficult to mix.

PACKAGING

500 ml aerosol (12 x 500 ml carton)