

# X-SIL

## HIGH PERFORMANCE SILICONE SPRAY

### DESCRIPTION

High quality & performance universal silicone based lubricant spray.

### BASIC BENEFITS

- Provides dry protective microfilm on surfaces.
- Avoids sticking of materials.
- Prevents stick-slip.
- Prevents freezing.
- Reduces static electricity.
- Protects against wear of hard on soft and soft on hard materials.
- Universal application.



### PROPERTIES

- Provides non-greasy and non-oily lubrication.
- Protects against rust and corrosion.
- Is water and moisture repellent.
- Does not stick, stain or oxidise.
- Harmless for the materials.

### APPLICATION

Can be used on different materials: plastic on metal, on wood, metal on metal, profile rubber, etc. Protects against jamming or freezing of doors, windows, sliding doors, etc.

On all sliding surfaces for a clean dry & invisible lubrication.

Do not use on material that will be painted or glued afterwards.

Shake well before use. Hold spray can approximately 20 - 30 cm from the applied surface.

Spray on to the surface. When needed, spread with a soft cloth. Leave to dry.

### TYPICALS

Form:	Aerosol
pH-value:	Not determined.
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	-44 °C
Flash point:	-97 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	200 °C
Decomposition temperature:	Not determined.
Vapour pressure at 20°C:	4 Bar
Density at 20°C:	0.653 g/cm <sup>3</sup>
Solubility in / Miscibility with water:	Not miscible or difficult to mix.

### PACKAGING

500 ml aerosol (12 x 500 ml carton)