

# XA-CVTF

## CONTINUOUSLY VARIABLE TRANSMISSION (CVT) FLUID

### DESCRIPTION

High performance synthetic fluid specially engineered for Continuously Variable Transmission (CVT) gearboxes. XA-CVTF is made of precisely selected base oils and special additives. Suitable for use in a wide range of vehicles equipped with CVT transmissions of both chain/pulleys or belt/pulleys design.

### PROPERTIES

- Allows fuel economy for cars fitted with CVT gearboxes by providing optimum metal-to-metal friction.
- Superior response through smooth shift feel and reduced shift time lag.
- Provides optimum anti-shudder performance and avoids engine vibrations.
- Improves cold temperature performance.
- Extremely high and stable viscosity index.
- Extended service interval in combination with a longer transmission life.
- Very good stability against oxidation and thermal properties.
- Strong reduction of wear, corrosion and foam.
- Ideal friction performance, for both CVT belt and CVT chain.



### APPLICATION

XA-CVTF is recommended for use in a wide range of CVT-Transmission types. Apply the recommended amount of oil as indicated in the manufacturer's service instructions. Wrong oil level could cause damage.

### TYPICALS

Density at 15 °C, kg/l	0,848
Viscosity 40 °C, mm <sup>2</sup> /s	38,00
Viscosity 100 °C, mm <sup>2</sup> /s	7,50
Viscosity Index	181
Flash Point COC, °C	214
Pour Point, °C	-48
Total Base Number, mgKOH/g	3,6

### PACKAGING

1L can (12 x 1L carton)  
60 L drum  
208 L drum

### SPECIFICATIONS

Toyota CVTF TC/FE  
Nissan NS-1/NS-2/NS-3  
Honda HMMF/HCF2  
Mitsubishi SP-III/CVTF-J1  
Subaru ECVT/iCVT  
Daihatsu Ammix CVT  
Suzuki CVTF TC/NS-2/CVT Green 1  
Hyundai SP-III  
Chrysler Jeep NS-2  
BMW Mini 83220136376/83220429159  
MB 236.20  
Ford WSS-M2C928-A  
VW G 052 180/G 052 516  
JASO M358  
Mopar CVTF+4