

VALVEX

UPPER CYLINDER PROTECTION LUBRICANT

DESCRIPTION

Valvex Protection Fluid is a high performance upper cylinder lubricant designed to minimize Valve Seat Recession in LPG and CNG Petrol engines.

BASIC BENEFITS

- Protects and lubricate valves and valve seats.
- Smoother engine running.
- Improved engine reliability.
- Self-mixing.

PROPERTIES

- No harmful effects on catalytic converters or the environment.
- Doesn't influence the octane number.
- Lubricates and creates a protective barrier between the valves and valve seats.
- Avoids mechanical damage caused by micro welding on the valve seats.
- Provides long lasting trouble free engine operation.
- Consist no lead.

APPLICATION

Specially designed for the VAP-Saver® Lubricator equipment. For all LPG and CNG equipped petrol engines. Safe to use in vehicles fitted with catalytic converters and oxygen sensors.

DIRECTIONS FOR USE

Adjust the dosage of the lubricant by using the adjusting screw of the VAP SAVER UNIT, while the engine is running at idle speed:

- 8 drops per minute for a 4 cylinder engine.
- 12 drops per minute for a 6 cylinder engine.
- 16 drops per minute for an 8 cylinder engine.

Afterwards, make sure the Valvex consumption reaches a minimum of:

- 0,5L per 1000 for a 4 cylinder engine.
- 0,75L per 1000 km for a 6 cylinder engine.
- 1L per 1000 km for an 8 cylinder engine.

Note: In heavy-duty conditions or for very sensitive engines: increase the dosage by 50%.

TYPICALS

Physical state:	liquid	Decomposition temperature:	Undetermined.
Colour:	green	Oxidizing properties:	not oxidizing.
pH-Value:	Not applicable.	Vapour pressure:	Undetermined.
Melting point:	Undetermined.	Density (at 20 °C):	0,861 g/cm ³
Initial boiling point and boiling range:	Undetermined.	Water solubility (at 20 °C):	not miscible
Flash point:	154 °C	Partition coefficient:	Undetermined.
Ignition temperature:	Undetermined.	Viscosity / kinematic (at 40 °C):	11,9 mm ² /s
Auto-ignition temperature:	Undetermined.	Evaporation rate (at 20 °C):	Undetermined.
Solid:	Undetermined.		
Gas:	Undetermined.		

PACKAGING

1L can (12 x 1L carton)

