

# CE300

## CERAMIC BOOSTER ADVANCED OIL ADDITIVE

### DESCRIPTION

CE300 is a new generation engine oil additive, which outperforms existing products due to technology that utilizes micro-ceramic lubricating particles. The micro-ceramic particles are very powerful solid lubricants that decrease the coefficient of friction and resist to the highest temperatures. The additive forms an extremely resistant protective film that substantially reduces wear. Even when the engine is not running, this film remains on the internal parts of the engine, ensuring optimum protection during cold starting.

### BASIC BENEFITS

- Increased power.
- Increases in fuel economy.
- Less engine noise.
- Decreases in oil consumption.
- Lowering of CO<sub>2</sub> emissions.

### PROPERTIES

- Reduces friction and wear.
- Prevents metal-to-metal contact under high load.
- Protects against corrosion, oxidation, rust and wear.
- Forms an extremely resistant protective film on internal engine parts.
- ZERO SAPS technology: preserves the Diesel Particle Filter (DPF).
- CE300 is compatible with all types of engine oils.
- Due to their nano-size, these ceramic particles are absolutely safe for oil filters.

### APPLICATION

CE300 is recommended for all petrol and diesel engines including all the latest engine technologies, such as: direct injection, common rail, turbo charged and catalytic converters, also compatible with older engine designs. Suitable for cars, trucks motorcycles and boats, as well as industrial engines.

### Recommendation:

For maximum effect and advisability first remove (before applying) the old deposits & acids from the system by cleaning it with M-Flush in the old oil.

### DIRECTIONS FOR USE

To be added at each oil change, 1 can (300 ml) is suitable for use with 2.5 to 5 liters of oil.

### TYPICALS

Physical state:	liquid	Decomposition temperature:	Undetermined.
Colour:	white	Oxidizing properties:	not oxidizing.
pH-Value:	Not applicable.	Vapour pressure:	Undetermined.
Melting point:	< 0 °C	Density (at 20 °C):	0,87 g/cm <sup>3</sup>
Initial boiling point and boiling range:	> 200 °C	Water solubility (at 20 °C):	partially soluble
Flash point:	> 110 °C	Partition coefficient:	Undetermined.
Ignition temperature:	Undetermined.	Viscosity / kinematic:	Undetermined.
		Evaporation rate (at 20 °C):	Undetermined.

### PACKAGING

300 ml can (12 x 300 ml carton)

