

X-CUT

HIGH PERFORMANCE CUTTING OIL REINFORCED WITH CERFLON®

DESCRIPTION

High performance adhesive multipurpose cutting oil containing the advanced Cerflon® reinforced lubricant.

BASIC BENEFITS

- Easy and precise drill.
- Extended life of cutting tools.
- High track.
- Perfect Finish.

PROPERTIES

- Excellent lubrication at high cutting speeds.
- Protects and improves service life of cutting tools in operation.
- Lower Friction; outstanding lubricating effect thanks to the Cerflon® reinforced lubricant.

APPLICATION

To be used when drilling, sawing or tapping steel and most nonferrous metals as well as stainless steel. Shake well before use. Wipe clean with a dry cloth.

TYPICALS

Form:	Aerosol
pH-value:	Not determined.
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	-44°C
Flash point:	-97 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	365°C
Decomposition temperature:	Not determined.
Vapour pressure at 20°C:	4 Bar
Density at 20°C:	0.761 g/cm ³
Solubility in / Miscibility with water:	Not miscible or difficult to mix.

PACKAGING

500 ml aerosol (12 x 500 ml carton)

